



PARTS INDEX

<i>ITEM</i>	<i>PART NUMBER</i>	<i>DESCRIPTION</i>	<i>SERVICE</i>
2,3	5240-20N	PLUG & SEAT ASSEMBLY, NYLON	EAN READY
4	5270-4PN	BONNET NUT, PLATED	EAN READY
5	5270-5N	PACKING	EAN READY
6	5240-6A	HANDWHEEL, EASY GRIP, BLACK	EAN READY
	5270-6AN	HANDWHEEL, EASY GRIP, GREEN	EAN READY
7	5203-7P	HANDWHEEL NUT	EAN READY
8	5270-8PN	STEM, PLATED	EAN READY
9	5240-9	SPRING	EAN READY
10	5240-10	HANDWHEEL WASHER	EAN READY
12	3990-3358N	SAFETY ASSEMBLY, 3358 PSI BURST FOR 2015 PSI SERVICE	EAN READY
	3990-3692	SAFETY ASSEMBLY, 3692 PSI BURST FOR 2215 PSI SERVICE	AIR
	3990-3750	SAFETY ASSEMBLY, 3750 PSI BURST FOR 2250 PSI SERVICE	AIR
	3990-4000N	SAFETY ASSEMBLY, 4000 PSI BURST FOR 2400 PSI SERVICE	EAN READY
	3990-4550N	SAFETY ASSEMBLY, 4550 PSI BURST FOR 2730 PSI SERVICE	EAN READY
	3990-5000N	SAFETY ASSEMBLY, 5000 PSI BURST FOR 3000 PSI SERVICE	EAN READY
	3990-5250N	SAFETY ASSEMBLY, 5250 PSI BURST FOR 3180 PSI FABER SERVICE PRESSURE OR 3442/3500 PSI PST SERVICE PRES-SURE	EAN READY
	3990-5500	SAFETY ASSEMBLY, 5500 PSI BURST FOR 3300 PSI SERVICE	AIR
	3990-5500N	SAFETY ASSEMBLY, 5500 PSI BURST FOR 3300 PSI SERVICE	EAN READY
	3990-7250N	SAFETY ASSEMBLY, 7250 PSI BURST FOR 4350 PSI SERVICE	AIR
14	5240-14	O-RING, INLET, 3/4-14 NPSM	AIR
	5240-14V	O-RING, INLET, VITON, 3/4-14 NPSM	EAN READY
	5280-14	O-RING, INLET, 7/8-14 UNF	AIR
	5280-14V	O-RING, INLET, VITON, 7/8-14 UNF	EAN READY
15	5270-15N	TUBE, PLATED	EAN READY
16	5270-16N	BONNET GASKET	EAN READY
17	3100-9	O-RING, STEM	AIR
	3100-9V	O-RING, STEM, VITON	EAN READY
	3100-9EP	O-RING, STEM, EPDM	EAN READY
19	5240-12	O-RING, K OUTLET	AIR
	5240-12V	O-RING, K OUTLET, VITON	EAN READY
	5240-12PU	O-RING, K OUTLET, POLYURETHANE	EAN READY



PARTS INDEX

23*	5440-23	O-RING, DIN/K ADAPTOR OUTLET, OUTER	AIR
	5440-23V	O-RING, DIN/K ADAPTOR OUTLET, OUTER, VITON	EAN READY
	5240-12PU	O-RING, DIN/K ADAPTOR OUTLET, OUTER, POLYURETHANE	EAN READY
		*SEE NOTE BELOW FOR CORRECT OUTER O-RING	
24	5440-23N	PRO DIN/K OUTLET ADAPTOR	EAN READY
25	5440-23	O-RING, DIN/K ADAPTOR OUTLET, INNER	AIR
	5440-23V	O-RING, DIN/K ADAPTOR OUTLET, INNER, VITON	EAN READY
26	5440-21(LH)	MODULAR VALVE SIDE PLUG FOR LEFT HAND VALVE	AIR
27	5440-21(RH)	MODULAR VALVE SIDE PLUG FOR RIGHT HAND VALVE	AIR
28	5440-250	O-RING, SIDE PLUG	AIR
	5440-250V	O-RING, SIDE PLUG	EAN READY
	5440-250EP	O-RING, SIDE PLUG, EPDM	EAN READY

*Note: For valves manufactured from December, 2004 through June, 2006 with lot numbers “12-04E” through “06-06E”, the correct outer o-ring is the 5240-12PU. All other PRO valve adaptor outer o-rings can be either the 5440-23 for Breathing Air use or the 5440-23V for EAN Ready use.

This can easily be determined by one of two methods.

1) Compare the inner & outer o-rings on valves with PRO outlet adaptors. If the outer o-ring is smaller than the inner o-ring, then the correct outer o-ring is the 5240-12PU. If the inner and outer o-rings are the same size, then the correct outer o-ring is the 5440-23 for Breathing Air use or the 5440-23V for EAN Ready use.

2) Measure the outside o-ring. The 5240-12PU o-ring has a thickness of .070 inch (1.8 mm) and an outside diameter of .629 inch (16 mm). The 5440-23 and 5440-23V have a thickness of .103 inch (2.6 mm) and an outside diameter of .693 inch (17.6 mm).